

# Declaration of Performance

## Gatic UltraSlot

Declaration of Performance No.	229
Issue & Date	Issue 1 - 1 <sup>st</sup> October 2019
Product	Gatic UltraSlot
Manufacturer's Address	Wade International Ltd - Third Avenue, Halstead, Essex, CO9 2SX United Kingdom Telephone: +44(0)1787 475151 Fax: +44(0)1787 475579 Web: <a href="http://www.gatic.com">www.gatic.com</a> Email: sales@wadeint.co.uk
Intended Use	Gatic UltraSlot For the catchment and drainage of surface water in areas for pedestrian and/or vehicular traffic.
Product Range	UA00325, UA00326, UA00327, UA00328, UA00329, UA00330, UA00331, UA00332, UA00333, UA00334, UA00335, UA00336, UA00337, UA00338, UA00339, UA00340, UA00341, UA00342, UA00343, UA00344, UA00345, UA00346, UA00347, UA00348
System of Attestation of performance:	System 3
Notified Body	NB 0086 - BSI Product Services
Type Test Report No.	285/4618749
1. Water Tightness - Jointing of Drainage Channels:	No Leakage
2. Load Bearing Capacity - Deflection Under Load	
Maximum Load	F900*
Permanent Set	NPD
3. Durability	NPD
Material	1.5/2.5/3mm Thick mild steel sheet grade 'DX51D' (Pre-Galvanised) Continuously hot dipped galvanised 'Z275' minimised spangled, passivated to 'BS EN 10346: 2009' [DX51D+Z275-M-A-C] (Fe P02 G Z275 MA C)
Applied Standard	EN 1433:2002 + A1 2005

This declaration herewith confirms that the described manufactured items comply with the relevant parts of BS EN 1433:2002 + A1 2005 for linear drainage channels in areas for pedestrian and/or vehicular traffic for the catchment and drainage of surface water, \*when installed in compliance with the manufacturer's installation instructions

*A J Becker*

Business Management and R&D Manager

